







PRIME STONE

PRODUCT	COLOR / REF	SIZE	PACKING
	PRIME STONE BIANCO SKU# PRS-BIA-306	30x60cm (12"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE BIANCO SKU# PRS-BIA-606	60x60cm (24"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE BIANCO SKU# PRS-BIA-612	60x120cm (24"x48")	2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE SABBIA SKU# PRS-SAB-306	30x60cm (12"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet

PRIME STONE

PRODUCT	COLOR / REF	SIZE	PACKING
	PRIME STONE SABBIA SKU# PRS-SAB-606	60x60cm (24"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE SABBIA SKU# PRS-SAB-612	60x120cm (24"x48")	2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE GRIGIO SKU# PRS-GRI-306	30x60cm (12"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE GRIGIO SKU# PRS-GRI-606	60x60cm (24"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet

PRIME STONE

PRODUCT	COLOR / REF	SIZE	PACKING
	PRIME STONE GRIGIO SKU# PRS-GRI-612	60x120cm (24"x48")	2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE NERO SKU# PRS-NER-306	30x60cm (12"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE NERO SKU# PRS-NER-606	60x60cm (24"x24")	8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet
	PRIME STONE NERO SKU# PRS-NER-612	60x120cm (24"x48")	2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet

PRIME STONE

TYPE	Glazed Porcelain	APPLICATION	Indoors / Outdoors / Wall / Floor
DESCRIPTION	A cement-effect porcelain tile collection with a strong urban appeal, Thanks to its matt finish and material effects, this is a stylish cosmopolitan series with technical characteristics that make it suitable for projects of all kinds.		
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully the instructions set by the manufacturer of the adhesive used.		
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.		
NOTE	To achieve the visual aspect of the product and given the artisanal procedure for production and raw materials used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.		

TECHNICAL SPECIFICATIONS		ISO	TEST METHOD	PASS/FAIL
	FROST RESISTANCE	ISO 10545-12	No Resist	Pass

PRIME STONE

CARACTERÍSTICAS TÉCNICAS Technical characteristics		NORMA DE ENSAYO TEST ESTANDAR UNE-ISO-10545	NORMA DE PRODUCTO PRODUCT STANDARD ISO 13006	VALORES PROMEDIA THE TILE COMPANY THE TILE COMPANY AVERAGE VALUES
	LONGITUD Y ANCHURA Length and width	10545-2	± 0.6%	± 0.1%
	GROSOR Thickness		± 5.0%	± 5.0%
	RECTITUD DE LOS LADOS Straightness of sides		± 0.5%	± 0.1%
	ORTOGONALIDAD Rectangularity		± 0.6%	± 0.1%
	PLANITUD DE LA SUPERFICIE Surface planarity		± 0.5%	±0.25%
	ABSORCIÓN DE AGUA Water absorption	UNE-EN-ISO 10545-3	≤ 0.5%	≤ 0.1%
	RESISTENCIA A LA FLEXIÓN Bending strength	UNE-EN-ISO 10545-4	MIN 35 N/MM2	52 N/MM2
	CARGA DE ROTURA Breakage load	UNE-EN-ISO 10545-4	MIN 1300 N	2000 N
	RESISTENCIA A LA ABRASIÓN PROFUNDA Deep abrasion resistance	UNE-EN-ISO 10545-6	MAX 175 MM3	120 MM3
	DILATACIÓN TÉRMICA Thermal expansion	UNE-EN-ISO 10545-8	METODO ENSAYO DISPONIBLE Test method available	
	RESISTENCIA AL HIELO Frost resistance	UNE-EN-ISO 10545-12	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A ATAQUES QUÍMICOS Resistance to chemical attack	UNE-EN-ISO 10545-13	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A LAS MANCHAS Resistance to staining	UNE-EN-ISO 10545-14	CONFORME A LAS NORMAS Complies with standards	CONFORME A LAS NORMAS Complies with standards